



## Metal Family

Enter Complete Part Number Here →

**Ordering Information** • Custom features available upon request,  
Contact your Trombetta sales rep before ordering.

-            
**X X X - X X X X - X X X**

Family	Coil Connection Configuration	High Current Stud	Coil Voltage	Bracket Type	Bracket Location	Duty Cycle	Contact Material	Sealing
9- Metal	0- Special (X Connection unit, 10-32 Std)	0- 5/16-24 SPDT and 5/16-24 Standard Length Studs	6- 6 Volt	1- Standard Slot	1- .770"	0- 100% Continuous	1- Copper	0- No Additional Sealing
	2- Grounded (1) 8-32 Stud	2- 1/4 -20 Stud	12- 12 Volt	2- Closed Holes	2- .880"	2- 20% Sustained	2- Silver Alloy Contacts	1- Resistant to dust, liquid
	3- Grounded (1) 10-32 Stud Standard	4- Standard Metals	15- 15 Volt	3- Closed Holes Stretched	3- .990"	6- 60% Sustained	3- Future Silver Material Defender	
	5- Grounded (1) 10-32 Stud + Spade	5- 5/16-24 Med Length (Metals)	24- 24 Volt	4- Narrow Slot	4- 1.000" Bracket Option 5 Only		5- Alloy Silver Plated Movable	
	7- Non-Grounded(2) 10-32 Studs Standard	6- 5/16-24 Long Length (Metals)	30- 30 Volt	5- Special	5- 1.160" Standard Location		6- Alloy Silver Plated Movable & Stationary	
	8- Non-Grounded(2) 10-32 Studs Long	7- 8mm Std Length (Metals only)	36- 36 Volt	6- KDS Special				

N88 W13901 Main Street • Suite 200 • Menomonee Falls, WI 53051  
p 262.251.5454 • f 262.251.5757 • email: sales@trombetta.com



www.trombetta.com